



Amerex Corporation

7595 Gadsden Hwy. Trussville, AL 35173 ♦ Ph: (205) 655-3271 ♦ Fax: 1-800-654-5980 ♦ e-mail: sales@amerex-fire.com

Model 775 150 LB. 3M™ Novec 1230™ WHEELED FIRE EXTINGUISHER



- Environmentally friendly 3M™ Novec™ 1230 Clean Agent (0 ODP - 1 GWP)
- Brass, chrome plated operating valve
- 125 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Quick release 40 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- Operating temperature range: -40° to +120° F.
- 6 year manufacturer's warranty

SPECIFICATIONS	150 LB. Novec 1230
Model Number	775
Agent	Novec 1230
Capacity (lbs.)	150
UL Rating	3A:80B:C
Shipping Weight (lbs.)	205 (empty) / 355 (filled)
Discharge Time (sec.)	31
Cylinder - DOT 4BW240	
Operating Press (psi)	125
Test Pressure (psi)	480
Burst Pressure (minimum - psi)	960
Discharge Range (ft.)	30
Hose Length (ft.)	40
Hose Diameter (in.)	.75
Wheels (Semi-pneumatic) (in.)	16 x 4
Height (in.)	59
Width (in.)	29
Depth (in.)	42