



# ABC Dry Chemical

Manufactured and Tested to  
ANSI/UL Standards  
ISO-9001:2000/ISO-14001:2004 Certified  
UL LISTED AND USCG APPROVED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ U/L & U.S. Coast Guard Listed
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label.

## Stored Pressure



**ABC or Multi-Purpose** extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

**6 YEAR WARRANTY**

SPECIFICATIONS	ABC Dry Chemical										
VALVES	ALUMINUM						BRASS, CHROME PLATED				
Size & Capacity (lbs.)	2 ½	5	5	6	10 Tall	20	5	6	10 Short	10 Tall	20
Application	Nozzle		Hose and Nozzle				Hose and Nozzle				
Model Number	B417 / B417T	B500 / B500T	B402 / B402T	B443	B456	A411	B424	B461	419	B441	423
U/L Rating	1A:10B:C	2A:10B:C	3A:40B:C	3A:40B:C	4A:80B:C	20A:120B:C	2A:10B:C	3A:40B:C	4A:80B:C	4A:80B:C	20A:120B:C
Shipping Wt. (lbs.)	5 ¼ / 5 ½	9 ¼ / 9 ½	9 ¼ / 9 ½	12 ¼	18	38	10 ½	13 ¼	19	19	39
Height (in.)	15 ½	15 ¼	15 ¼	16	20	23 ¾	15 ½	16 ¼	17 5/8	20 ½	24
Width (in.)	5 ¼	7 ¼	7 ¼	7 ¼	7 ¼	10 ¼	8	8 ½	9 ½	8 ¾	10 ¼
Depth (Diam. - in.)	3	4 ¼	4 ¼	5	5	7	4 ¼	5	6	5	7
Range (ft.)	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	14	14	14 ½	20	30	14	14	22	20	30
Available with Chrome Plated Cylinder	YES	YES	YES		YES			YES	YES	YES	
F. M. Approved	YES	YES		YES	YES	YES		YES	YES	YES	YES
Standard Bracket	Wall / Vehicle-Marine			Wall			Wall				

