



Carbon Dioxide

**Manufactured and Tested to
ANSI/UL Standards**
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED, FM AND USCG APPROVED

- ★ Rust free aluminum cylinders - up to 30% lighter than steel cylinders
- ★ All Metal Valve Construction
- ★ Meets many hospital medical equipment requirements
- ★ Independently tested and approved for use in MRI facilities (Model 322NM)
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -40°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label

SPECIFICATIONS	CARBON DIOXIDE			
	5	10	15	20
Size & Capacity (lbs.)	5	10	15	20
Application	Horn	Hose & Horn		
Model Number	322	330	331	332
U/L Rating	5B:C	10B:C	10B:C	10B:C
Shipping Weight (lbs.)	14	28¾	37¾	50¾
Height (in.)	17¾	24	30	30
Width (in.)	8¾	12	12	13
Depth (Diam. - in.)	5½	7	7	8
Range (ft.)	3- 8			
Discharge Time (sec.)	10	10	12½	19
F. M. Approved	Yes			
Standard Bracket	Wall			



Carbon Dioxide is discharged as a white cloud of "snow" which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

**Also available in 50 / 100 lb.
wheeled extinguishers and
100 lb. stationary.**

5 YEAR WARRANTY

