



# Halotron

Manufactured and Tested to  
ANSI/UL Standards  
ISO-9001:2000/ISO-14001:2004 Certified  
UL LISTED AND USCG APPROVED\*

FAA Approved Model Available  
(Model B394TS)

## RUGGED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction

## ENVIRONMENTALLY ACCEPTABLE

- ★ EPA approved "Clean Agent" for Class A, B and C hazards
- ★ Low GWP (Global Warming Potential)
- ★ Low ODP (Ozone Depletion Potential)
- ★ Short Atmospheric Lifetime

## CLEAN

- ★ Leaves no residue

## USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ No electrical conductivity back to the operator
- ★ No thermal or static shock
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -40°F to 120°F)

\* Note: 5 lb., 11 lb. and 15 ½ lb. extinguishers are USCG approved with the bracket listed on the UL label.

## Stored Pressure



FAA Approved  
(Model B394TS)



Models  
397  
398

Models  
A384T  
B385TS  
B386T  
B394TS

HALOTRON I is a "Clean Agent" HydroChloroFluoroCarbon (HCFC) discharged as a rapidly evaporating liquid which leaves no residue. It effectively extinguishes Class A and B fires by cooling and smothering and it will not conduct electricity back to the operator. Halotron is pressurized with Argon gas and is an EPA and FAA approved agent suitable for use on Class A, B and C fires. It has a *low* GWP of 0.04 - 0.24, *low* ODP of 0.014 (twelve times lower than the EPA maximum allowable ODP of 0.20) and a *low* Atmospheric Lifetime (3½ to 11 years).

Halotron is intended for use in areas formerly protected by Halon 1211 hand portable extinguishers such as computer rooms, telecommunications facilities, clean rooms, data storage areas, offices (for protection of sensitive electronic equipment), boats and vehicles.

AVAILABLE IN WHEELED EXTINGUISHERS  
5 YEAR WARRANTY



SPECIFICATIONS	HALOTRON I					
	VALVES		ALUMINUM		BRASS, CHROME PLATED	
Size & Capacity (lbs.)	1.4	2½	5	5½	11	15½
Application	Nozzle			Hose & Nozzle		
Model Number	A384T	B385TS	B386T	B394TS	397	398
UL & ULC Rating	1B:C	2B:C	5B:C	5B:C	1A:10B:C	2A:10B:C
Shipping Weight (lbs.)	3¼	5¼	9½	10	22½	27½
Height (in.)	10	15½	15¼	15	21 7/8	21 7/8
Width (in.)	3¼	6 3/8	5¼	5 1/8	9¼	9¼
Depth (Diam. - in.)	2 5/8	3	4¼	4¼	6	6
Range (ft.)	6 - 8	6 - 10	9 - 15	9 - 15	9 - 15	12 - 18
Discharge Time (sec.)	9	9	9	9	9	14
Available with Chrome Plated Cylinder	Yes	Yes	Yes			
Minimum Space Requirement (cu. ft.)	196	350	700	770	1540	2170
Standard Bracket	Vehicle	Vehicle	Vehicle	Aircraft	Wall	Wall