



Water & Foam

**Manufactured and Tested to
ANSI/UL Standards**

**Amerex is an ISO-9001:2000
Registered Firm**

RUGGED

- ★ Polished Stainless Steel Cylinders
- ★ All Metal Valve Construction

CLEAN

- ★ Leaves no powder residue

USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ Novice friendly, easy to understand instructions
- ★ Bar Coded Labels

(Temperature Range +40°F to 120°F)

Note: The Model 240 may be freeze protected to -40°F by adding a Model 506 Anti-Freeze charge

SPECIFICATIONS	WATER	AFFF FOAM	FFFP FOAM
	Hose and Nozzle	Hose and Spray Nozzle	Hose and Air Aspirated Nozzle
Model Number	240	254	252
UL Rating	2A	2A:10B	3A:20B
Capacity	2½ Gal.	6 Liter	2½ Gal.
Shipping Wt. (lbs.) (Empty)	7 ½	8	11
Height (in.)	24 ½	19	24 ½
Width (in.)	9	8	9
Depth (Diam. - in.)	7	7	7
Range (Initial - ft.)	45 - 55	10 - 12	10 - 12
F. M. Approved	Yes		Yes
Discharge Time (sec.)	50	60	55
Standard Bracket		Wall	

Stored Pressure



**Model
240**



**Model
254**

**Model
252
250**



Model 240 utilizes the cooling, soaking and penetrating effect of a 45-55 ft. stream of WATER. The 50 sec. discharge time makes it very effective for inexperienced operators for use on Class A fires. Protect from freezing by adding the Model 506 Loaded Stream/Anti-freeze charge. In areas with a high level chloride content water it may be corrosion protected by using the Model 507 charge.

Model 254 AFFF FOAM unique 6 liter size fills many requirements for a lighter, more compact Class A:B extinguisher. Easy and effective application with the patented spray nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

Model 252 FFFP FOAM adds Class B fire fighting capability to the Class A effectiveness of this extinguisher. The *Alcohol Resistant* fire fighting agent is effective on fires in a wide variety of Class B materials such as alcohols, polar solvents, hydrocarbons and combinations such as gasohol. Apply to a non-ignited Class B liquid spill and it will seal the surface minimizing the chance of serious fire.

Model 250 AFFF FOAM Class A:B extinguisher. Easy and effective application with air aspirated nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

Available in a 33 Gal. FFFP Wheeled or Stationary unit.

U.L. LISTED - 6 YEAR WARRANTY

